

# 食品级橡胶管

## A1-201

FOOD 10 OIL SD 



### 应用:

- 用于油脂性食品物料的输送和抽吸。

### 技术参数:

- 内层: 食品级, 耐油脂NBR合成橡胶, 白色, 光滑
- 增强层: 合成纤维编织网并嵌入螺旋钢丝增强
- 外层: 耐老化、耐油合成橡胶, 蓝色布纹
- 工作温度: -20° C 至 +85° C

### 适用标准及认证:

- FDA

### Applications:

- Food suction and delivery hose, suitable for oily and fatty products.

### Technical Description:

- Tube: Food grade, oil resistant NBR synthetic rubber, white, smooth
- Reinforcement: Synthetic textile with embedded steel helix
- Cover: Weather and oil resistant synthetic rubber, blue, fabric impression
- Temperature range: -20°C to +85°C

### Standard/Approval:

- Standard/Approval: FDA compliant tube

产品编码 No.	内径 in	mm	外径 mm	工作压力 bar	爆破压力 bar	真空度 bar	弯曲半径 mm	重量 kg/m	包装长度 m
A1-201-0750	3/4"	19	30	10	30	0.9	80	0.65	40
A1-201-1000	1"	25	36	10	30	0.9	100	0.87	40
A1-201-1500	1 1/2"	38	50	10	30	0.9	160	1.22	40
A1-201-2000	2"	51	64	10	30	0.9	200	1.76	40
A1-201-2500	2 1/2"	63	77	10	30	0.9	240	2.3	40
A1-201-3000	3"	76	90	10	30	0.9	320	2.89	40

**blueFuture**

您身边的工业专家