

耐低温水气管 A4-011



应用:

是固特异最广泛使用的耐低温的胶管, 可在- 54° C的环境下, 可用于输送空气, 水, 油, 煤油, 燃料, 以及一些化学品。

技术参数:

- 内层: 丁腈合成橡胶, RMA Class A (高耐油性)
- 增强层: 合成纤维, 带导线防静电
- 外层: 氯丁橡胶, RMA Class A
- 温度: -54° C到82° C
- 包装: 500' 一卷, 每卷最多分成3条, 每条最短50'

Applications:

This is our most popular cold temperature multipurpose hose. For use with air, water, oil, kerosene, fuel oil and some chemical applications.

Technical description:

- Tube: Nitrile synthetic rubber, RMA Class A (High Oil Resistance)
- Reinforcement: One textile braid
- Cover: Neoprene, RMA Class A (High Oil Resistance)
- Temperature: -54°C to 82°C
- Packaging: 500' reels, maximum 3 pieces, 50' minimum length

产品编码 No.	内径 in.	mm	外径 mm	工作压力 bar	重量 kg/m	包装长度 m
A4-011-0250	1/4"	6.4	16.0	20.7	0.22	152.4
A4-011-0380	3/8"	9.5	19.1	20.7	0.28	152.4
A4-011-0500	1/2"	12.7	23.1	20.7	0.37	152.4
A4-011-0750	3/4"	19.1	30.0	20.7	0.54	152.4
A4-011-1000	1"	25.4	38.1	20.7	0.86	152.4
A4-011-1250	1-1/4"	31.8	45.7	20.7	1.1	152.4
A4-011-1380	1-3/8"	34.9	50.0	20.7	1.37	152.4
A4-011-1500	1-1/2"	38.1	53.1	20.7	1.50	152.4

blueFuture
您身边的工业专家