

# 葡萄酒排吸管

## A5-005



### 应用:

- 用于水、葡萄酒、啤酒、果汁和软饮料的抽吸和输送，广泛应用于酿酒工厂

### 材料:

- 内层: 白色食品级合成橡胶
- 增强层: 合成纤维层, 螺旋钢丝加强
- 外层: 光滑、红色、耐磨、抗老化和氧化布纹合成橡胶

### 温度:

- 40° C + 120° C

### 适用标准及认证:

- FDA 21CFR,177.2600  
BFR RECOMMENDATION XXI CAT2  
DM21.03.73 E SEGUENTI  
JAPAN-MINISTRY OF HEALTH AND WELFARE  
NOTICE NO.370,1959 AND NO. 201,2006  
3A Sanitary Standard Class II  
RAL REGISTRATION G-74.

### Applications:

- Suction and delivery hose for transporting water, wine, beer, juice and soft drinks, excellent choice for brewery and winery applications

### Material:

- Tube: White, smooth, food quality
- Reinforcement: High tensile textile cord, dual galvanized steel helix
- Cover: Red, smooth with cloth impression, resistant to weather, ozone and abrasion

### Temperature:

- 40°C to +120°C

### Standard/Approval:

- FDA 21CFR,177.2600  
BFR RECOMMENDATION XXI CAT2  
DM21.03.73 E SEGUENTI  
JAPAN-MINISTRY OF HEALTH AND WELFARE  
NOTICE NO.370,1959 AND NO. 201,2006  
3A Sanitary Standard Class II  
RAL REGISTRATION G-74.

## 葡萄酒排吸管 VINTNER

产品编码 No.	内径 in	mm	外径 mm	工作压力 bar	爆破压力 bar	弯曲半径 mm	重量 kg/m	包装长度 m
A5-005-0750	3/4"	19.1	31	10.3	30	60	0.7	40
A5-005-1000	1"	25.4	37	10.3	30	85	0.85	40
A5-005-1250	1-1/4"	31.8	44	10.3	30	115	1.04	40
A5-005-1500	1-1/2"	38.1	51	10.3	30	150	1.31	40
A5-005-2000	2"	50.8	64	10.3	30	210	1.69	40
A5-005-2500	2-1/2"	63.5	78.5	10.3	30	265	2.55	40
A5-005-3000	3"	76.2	91	10.3	30	320	2.99	40
A5-005-4000	4"	101.6	118	10.3	30	430	4.18	40

blueFuture

您身边的工业专家