

# 光滑特氟龙软管

## AX-002



### 应用:

- 医药行业, 食品行业, 化学行业等

### 优点:

- 里层为完全平滑的PTFE软管, 外覆SS304 不锈钢编织
- 具有柔韧性高、零摩擦、耐高压和耐温广的优势
- 标准与防静电内衬可供选择

### 温度范围:

- -70℃至+260℃

### 温度范围:

- 符合FDA 和USP 认证

### Applications:

- For pharmaceutical, food, chemical, beverage and almost endless list of applications

### Advantages:

- Smooth bore PTFE hose, with 304 stainless steel over braid
- High performance product offering superb flexibility, zero friction, high pressure and a wide temperature range
- Virgin and anti-static liners available

### Temperature:

- -70 C to +260 C

### Temperature:

- FDA and USP compliant

## 光滑特氟龙软管 T1B

产品编码 No.	Size mm	内径		外径		内衬壁厚 mm	工作压力 bar	爆破压力 bar	弯曲半径 mm	重量 kg/m
		min	max.	min	max.					
AX-002-0190	4.9	4.65	5.16	7.32	8.43	0.90	276	828	51	0.090
AX-002-0200	5.1	4.85	5.36	7.49	8.61	0.90	264	793	64	0.094
AX-002-0260	6.7	6.45	6.96	8.83	9.86	0.75	224	672	76	0.092
AX-002-0330	8.4	8.15	8.66	10.54	11.56	0.65	207	621	102	0.141
AX-002-0410	10.3	9.93	10.64	12.78	14.10	0.65	183	552	133	0.148
AX-002-0530	13.4	13.06	13.36	15.88	17.22	0.90	161	483	152	0.249
AX-002-0650	16.6	16.10	17.12	18.95	20.57	0.90	114	345	178	0.290
AX-002-0780	19.8	19.30	20.32	22.15	23.77	1.00	103	310	203	0.339
AX-002-0870	22.1	21.59	22.61	24.46	26.09	1.00	92	276	229	0.382
AX-002-1030	26.1	25.60	26.62	28.45	30.07	1.20	80	241	305	0.461

**blueFuture**

您身边的工业专家