

# 波纹特氟龙软管

## AX-003



### 应用:

- 医药行业, 食品行业, 化学行业等

### 优点:

- 里层为波纹状的PTFE软管, 外覆SS304不锈钢编织
- 质轻, 非常柔软, 易清洗, 易排水, 应用范围非常广
- 防静电内衬

### 温度范围:

- -70°C至+260°C

### 温度范围:

- 符合FDA和USP认证

### Applications:

- For pharmaceutical, food, chemical, beverage and an almost endless list of applications

### Advantages:

- Lightweight, highly flexible, convoluted PTFE hose, with 304 stainless steel over braid
- Low profile liner self-draining, easy clean solution for a wide range of applications
- Anti-static liners

### Temperature:

- -70 C to +260 C

### Temperature:

- FDA and USP compliant

## 波纹特氟龙软管 TCB1AE

产品编码 No.	Size in.	内径		外径		内衬壁厚 mm	工作压力 bar	爆破压力 bar	弯曲半径 mm	重量 kg/m
		min	max.	min	max.					
AX-003-0250	1/4"	6.10	6.70	9.30	9.90	0.75	172	517	18	0.140
AX-003-0310	5/16"	7.90	8.50	12.30	12.90	0.60	138	414	20	0.160
AX-003-0380	3/8"	9.50	10.20	12.80	14.50	0.65	138	414	20	0.152
AX-003-0500	1/2"	12.45	13.08	17.80	19.20	0.80	103	310	25	0.253
AX-003-0630	5/8"	15.70	16.38	21.80	24.00	0.80	83	248	51	0.304
AX-003-0750	3/4"	19.00	19.65	24.00	27.00	1.00	69	207	64	0.374
AX-003-0870	7/8"	21.84	22.86	27.94	29.46	1.00	57	172	76	0.460
AX-003-1000	1"	25.50	26.16	32.20	36.10	1.00	46	138	89	0.543
AX-003-1250	1-1/4"	31.95	32.46	40.20	41.30	1.00	34	103	125	0.635
AX-003-1500	1-1/2"	38.00	38.90	47.80	49.00	1.00	30	90	152	0.840
AX-003-2000	2"	50.90	51.90	60.50	62.30	1.10	23	69	200	1.000

**blueFuture**

您身边的工业专家