

耐真空波纹特氟龙软管 AX-006



优点:

- 口径: 1/2" 到 2", 符合 DIN26054-1
- 温度范围: -70°C 至 +260°C
- 标准与防静电内衬可供选择, 通过 ATEX 认证
- 里层为浅度波纹状 PTFE 软管, 内置不锈钢螺旋钢丝加强, 外覆 SS304 不锈钢编织
- 柔韧性高, 抗扭结, 即使在高温时都有极好的耐高压和耐真空性能, 符合 FDA 和 USP 认证
- 特别适用于粘性介质的输送及对清洁要求很高的场合

Advantages:

- Range 1/2"-2" (DN12-DN50) hose in accordance to DIN 26054-1.
- Virgin and anti-static liners available, ATEX Certified
- A low profile (shallow), heavy walled, convoluted PTFE hose, with external stainless steel vacuum spiral and 304 stainless steel over braid as standard
- Excellent vacuum and pressure ratings, even at elevated temperatures

Applications:

- Choose when hygienic cleaning, transfer of heavy viscous products/liquids and adhesive are areas of particular concern.

耐真空波纹特氟龙软管 AX-006

产品编码 No.	Size in.	内径		外径		内衬壁厚 mm	工作压力 bar	爆破压力 bar	弯曲半径 mm	真空度 bar	重量 kg/m	包装长度 m
		min	max.	min	max.							
AX-006-0500	1/2"	10	10.9	18.2	19.1	1.25	60	300	38	0.887	0.33	15
AX-006-0630	5/8"	12	12.9	21.2	22.1	1.25	55	270	46	0.887	0.38	15
AX-006-0750	3/4"	15	15.9	26.1	27.0	1.50	60	290	51	0.887	0.45	15
AX-006-1000	1"	20	20.9	30.9	31.8	1.50	40	210	70	0.887	0.70	15
AX-006-1250	1-1/4"	25	25.9	38.9	39.8	1.50	40	210	82	0.887	0.82	15
AX-006-1500	1-1/2"	32	32.9	44.1	45.0	1.50	35	175	100	0.887	1.50	15
AX-006-2000	2"	42	42.9	57.9	58.8	1.65	25	135	140	0.887	2.10	15

防静电软管可供选择

blueFuture

您身边的工业专家