


食品级轻型物料PU软管 PL-021



颜色:

- 透明,带螺旋状镀铜钢丝加强

温度:

- 40°C / + 90°C (短时间可耐受 125°C)

技术特性:

- 聚酯型聚氨酯软管,带螺旋状镀铜钢丝加强。壁厚范围均为 0.4 毫米。非常柔软,可压缩(压缩比为 5:1),更便于存储、运输和搬运。耐磨损、耐矿物油且具有良好的耐候、耐臭氧以及耐老化性能。特别适用于动态的工作环境。不含卤素,符合 RoHS 环保规范。钢丝接地可排静电,符合 TRB S2153 的排静电标准。

应用:

- 可排吸小颗粒、碎料、磨损性粉末以及化学粉末等。主要用于木工车间、陶瓷车间、水泥车间等粉尘比较大的生产环境的通风吸尘,特别适合需要摆动的部位。也可作为保护套管使用。根据欧盟 EC 食品接触标准,该软管也可用于输送干性食品。

Colour:

- Transparent with coppered spiral

Temperature range:

- 40°C + 90°C

Features:

- Ester based PU duct reinforced with a coppered steel spiral. Very flexible, and axially compressible (about 5:1) for easy handling and cost effective stock and transporting. Resistant to abrasion, mineral oils, ageing, ozone and aging. Halogen free, conform to RoHS, can be made antistatic in accordance with TRB S 2153 by grounding the spiral.

Applications:

- Woodworking, dedusting, vapours, small industrial cleaning and suction plants. Can be used as protection sleeve. Suction dry food according to EC Directives.

食品级轻型物料PU软管 PL-021

产品编码 No.	内径 in.	mm	壁厚 mm	耐负压 mH2O	弯曲半径 mm	体积 m³	重量 kg/m	包装长度 m
PL-021-1000	1"	25	0.4	0.4	25	0.054	0.130	10
PL-021-1180	*	30	0.4	0.4	25	0.062	0.150	10
PL-021-1250	1-1/4"	32	0.4	0.4	25	0.066	0.160	10
PL-021-1500	1-1/2"	38	0.4	0.4	30	0.076	0.185	10
PL-021-1580	1-9/16"	40	0.4	0.4	32	0.079	0.195	10
PL-021-1770	*	45	0.4	0.4	36	0.092	0.215	10
PL-021-2000	2"	51	0.4	0.4	40	0.108	0.205	10
PL-021-2360	2-3/8"	60	0.4	0.4	50	0.137	0.235	10
PL-021-2500	2-1/2"	63	0.4	0.4	55	0.150	0.245	10
PL-021-2560	2-9/16"	65	0.4	0.4	56	0.162	0.255	10
PL-021-2760	2-3/4"	70	0.4	0.4	60	0.181	0.360	10
PL-021-3000	3"	76	0.4	0.4	65	0.232	0.390	10
PL-021-3150	3-1/8"	80	0.4	0.4	65	0.254	0.405	10
PL-021-3540	3-5/8"	90	0.4	0.4	75	0.294	0.455	10
PL-021-4000	4"	102	0.4	0.3	85	0.286	0.510	10
PL-021-4330	*	110	0.4	0.3	90	0.318	0.550	10
PL-021-4530	4-1/2"	115	0.4	0.3	95	0.331	0.575	10
PL-021-4720	*	120	0.4	0.25	100	0.369	0.595	10
PL-021-5000	5"	127	0.4	0.25	105	0.402	0.630	10
PL-021-5120	*	130	0.4	0.2	105	0.424	0.645	10
PL-021-5510	*	140	0.4	0.2	115	0.500	0.695	10
PL-021-6000	6"	152	0.4	0.2	125	0.541	0.750	10
PL-021-6300	*	160	0.4	0.15	130	0.659	0.870	10
PL-021-7090	*	180	0.4	0.15	150	0.846	0.975	10
PL-021-8000	8"	203	0.4	0.1	165	1.140	1.100	10
PL-021-8660	*	220	0.4	0.1	185	0.898	1.190	10
PL-021-8980	9"	228	0.4	0.1	185	0.929	1.230	10
PL-021-10000	10"	254	0.4	0.1	210	1.184	1.370	10
PL-021-12000	12"	305	0.4	0.08	250	1.613	1.640	10
PL-021-12400	*	315	0.4	0.07	275	1.664	1.695	10
PL-021-14000	14"	356	0.4	0.07	300	待定	1.910	待定
PL-021-16000	16"	406	0.4	0.06	350	待定	2.175	待定

blueFuture
您身边的工业专家