

长寿命TPV材质蠕动泵管 Pharm-A-Line 9508



应用:

- 诊断设备
- 蠕动泵
- 生物反应器生产线
- 缓冲溶液 (酸和碱)
- CIP化学转移
- 净化线
- 无菌填充
- 疫苗生产

优势:

- 优异的泵寿命
- 优异的耐化学性
- 低粒子散裂
- 非溶血性
- 低渗透性
- 医用级材料
- 高温高压灭菌

技术参数:

- 材质: 医用级热塑性硫化橡胶
- 提供多种尺寸
- 温度范围: -60°F至 270°F (-50°C至130°C)

认证:

- 符合USP VI级测试
- ISO 10993第4和第5部分
- Title 21 CFR 177.2600
- 符合BSE / TSE标准
- 符合REACH标准
- 符合RoHS

灭菌方法:

- 高压灭菌器
- CIP清洗
- 环氧乙烷
- γ射线

Applications:

- Diagnostic Equipment
- Peristaltic Pumps
- Bio-Reactor Process Lines
- Buffer Solutions (acids and bases)
- CIP Chemical Transfer
- Purification Lines
- Sterile Fill
- Vaccine Production

Advantages:

- Superior Pump Life
- Excellent Chemical Resistance
- Low Particle Spallation
- Non Hemolytic
- Low Permeability
- Medical Grade Material
- Autoclavable

Technical Description:

- Material : Medical Grade Thermoplastic TPV
- Available in a wide Range of Sizes
- Temperature Range: -60°F to 270°F (-50 C to 130 C)

Approval:

- Meets USP Class VI Testing
- ISO 10993 Parts 4 and 5
- Title 21 CFR 177.2600
- BSE/TSE Compliant
- REACH Compliant
- RoHS Compliant

Sterilization:

- Autoclave
- Clean In Place (CIP)
- Ethylene Oxide (ETO)
- Gamma Irradiation

长寿命TPV材质蠕动泵管 9508

产品编码 No.	内径		壁厚		外径	
	in.	mm	in.	mm	in.	mm
9508-003	3/16"	4.8	1/16"	1.6	5/16"	7.9
9508-013	1/32"	0.8	1/16"	1.6	5/32"	4
9508-014	1/16"	1.6	1/16"	1.6	3/16"	4.8
9508-015	3/16"	4.8	3/32"	2.4	3/8"	9.6
9508-016	1/8"	3.2	1/16"	1.6	1/4"	6.4
9508-017	1/4"	6.4	1/16"	1.6	3/8"	9.6
9508-018	5/16"	7.9	1/16"	1.6	7/16"	11.2
9508-024	1/4"	6.4	3/32"	2.4	7/16"	11.2
9508-025	3/16"	4.8	1/16"	1.6	5/16"	7.9
9508-026	1/4"	6.4	1/8"	3.2	1/2"	12.7
9508-035	5/16"	7.9	3/32"	2.4	1/2"	12.7
9508-073	3/8"	9.6	3/32"	2.4	9/16"	14.4
9508-081	3/8"	9.6	1/8"	3.2	5/8"	16
9508-082	1/2"	12.7	1/8"	3.2	3/4"	19.1
9508-089	5/8"	15.9	3/16"	4.8	1"	25.4
9508-090	3/4"	19.1	3/16"	4.8	1-1/8"	28.6
9508-096	3/8"	9.6	1/16"	1.6	1/2"	12.7
9508-191	3/4"	19.1	3/16"	4.8	1-1/8"	28.6

