

网纹食品管 TFB型

PX-011



应用:

- 最适用于食品、饮料、油脂食品(使用非邻苯增塑剂)
- 柔软、使用方便, 最适用于活动部分的配管
- 耐油性优异, 最适用于食品用途以外的耐油配管
- 透明度高, 可确认流体, 放心可靠
- 符合日本食品卫生法、符合RoHS2修正规制, 安全放心

技术参数:

- 主材质: 软质聚氯乙烯
- 加强材料: 聚酯丝
- 颜色: 天然透明带绿色线条
- 包装: TFB-6~25: 筒卷 TFB-32~50: 薄膜卷
- 工作温度: -5°C至+70°C

优点:

- 耐热 (70°C)
- 适用于油脂类食品
- 非邻苯配方
- 泵送用

Applications:

- Most suitable for food, beverages, oily foods (using non-phthalic plasticizers)
- Soft, easy to use, most suitable for piping of movable parts
- Excellent oil resistance, most suitable for oil-resistant piping other than food applications
- High transparency, fluid can be confirmed, rest assured and reliable
- Comply with Japanese Food Sanitation Law and RoHS2 revision regulations, safe and secure

Technical description:

- Main material: soft polyvinyl chloride
- Reinforcing material: polyester silk
- Color: natural transparent with green lines
- Packing: TFB-6~25: roll TFB-32~50: film roll
- Working temperature: -5 C to +70 C

Advantages:

- Heat resistance (70 C)
- Suitable for oily food
- Non-phthalic formula
- For pumping

网纹食品管 TFB型

PX-011

产品编码 No.	内径 in	mm	外径 mm	使用压力 Mpa	标准长度重量 kg/卷	标准长度 m	最小弯曲半径 mm
PX-011-6	1/4"	6	11	0~1.0	9	100	30
PX-011-8	5/16"	8	13.5	0~1.0	13	100	40
PX-011-9	3/8"	9	15	0~1.0	15	100	45
PX-011-10	13/32"	10	16	0~1.0	16	100	50
PX-011-12	1/2"	12	18	0~0.8	19	100	65
PX-011-15	5/8"	15	22	0~0.8	27	100	95
PX-011-19	3/4"	19	26	0~0.6	16	50	120
PX-011-25	1"	25	33	0~0.6	25	50	165
PX-011-32	1-1/4"	32	41	0~0.4	35	50	200
PX-011-38	1-1/2"	38	48	0~0.4	45	50	300
PX-011-50	2"	50	62	0~0.3	54	40	440

