



# 水气多用途软管 WAS EPDM



## 应用用途:

用于一般工业应用, 适用于空气、水、油等不同场合, 不适合输送化学品或者磨损性介质

## 工作温度:

-40°C至+100°C

## 产品结构:

- 内层: 黑色EPDM合成橡胶, 光滑, 绝缘不导电
- 增强层: 高强度合成线绳
- 外层: 红/蓝/黄/黑/绿色可选, EPDM合成橡胶, 光滑, 耐风化

## 参数表格:

产品编码 No.	内经 in	mm	外径 mm	工作压力 bar	爆破压力 bar	包装长度 m
WAS EPDM-0190	3/16"	4.8	12.0	20.7	62	100
WAS EPDM-0250	1/4"	6.4	13.0	20.7	62	100
WAS EPDM-0310	5/16"	7.9	15.0	20.7	62	100
WAS EPDM-0380	3/8"	9.5	17.0	20.7	62	100
WAS EPDM-0500	1/2"	12.7	21.5	20.7	62	100
WAS EPDM-0630	5/8"	15.9	26.0	20.7	62	100
WAS EPDM-0750	3/4"	19.1	29.0	20.7	62	100
WAS EPDM-1000	1"	25.4	36.0	20.7	62	100
WAS EPDM-1250	1-1/4"	31.8	44.0	20.7	62	30
WAS EPDM-1500	1-1/2"	38.1	54.0	20.7	62	30
WAS EPDM-2000	2"	50.8	66.0	20.7	62	30